

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Label-Off**

Print date: 21.05.2015

Product code: 134

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Label-Off

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Uses advised against**

Reserved for industrial and professional use.

**1.3. Details of the supplier of the safety data sheet**

Company name:	ITW LLC & Co. KG	
Street:	Mühlackerstrasse 147	
Place:	D-75417 Mühlacker	
Telephone:	++49(0)7041-96340	Telefax: ++49(0)7041-963429
e-mail:	info@itwcp.de	
Internet:	www.itwcp.de	
Responsible Department:	Produktsicherheit	

**1.4. Emergency telephone number:** ++49(0)7041-96340  
Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Directive 67/548/EEC or 1999/45/EC**

Indications of danger: F+ - Extremely flammable, Xi - Irritant, N - Dangerous for the environment

R phrases:

Extremely flammable.

Irritating to skin.

May cause sensitisation by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard categories:

Flammable gas: Flam. Gas 1

Skin corrosion/irritation: Skin Irrit. 2

Respiratory/skin sensitization: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Hazardous components which must be listed on the label**

Hydrocarbons, C6, Isoalkane, D-Limonen

Signal word: Danger

Pictograms: GHS02-GHS07-GHS09

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Label-Off**

Print date: 21.05.2015

Product code: 134

Page 2 of 8


**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P302+P352	IF ON SKIN: Wash with plenty of water.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
265-151-9	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	40-70 %
64742-49-0	F - Highly flammable, Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R11-38-51-53-65	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411	
01-2119484651-34		
227-813-5	(R)-p-mentha-1,8-diene, d-limonene	10-30%
5989-27-5	Xi - Irritant, N - Dangerous for the environment R10-38-43-50-53	
601-029-00-7	Flam. Liq. 3, Skin Irrit. 2, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 1); H226 H315 H317 H400 H410	
919-857-5	Hydrocarbons, C9-C11, n-Alkane, iso-Alkane	10-30%
64742-48-9		
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304	
01-2119463258-33		
204-696-9	Carbondioxide	2,5-10 %
124-38-9		
	Compressed gas; H280	
200-578-6	ethanol, ethyl alcohol	<1%
64-17-5	F - Highly flammable R11	
603-002-00-5	Flam. Liq. 2; H225	

Full text of R-, H- and EUH-phrases: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Label-Off**

Print date: 21.05.2015

Product code: 134

Page 3 of 8

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

No data available

**After inhalation**

Provide fresh air.

**After contact with skin**

After contact with skin, wash immediately with: Water. Change contaminated clothing.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water.

**After ingestion**

If swallowed, immediately drink: Water.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>). Foam. Extinguishing powder.**Unsuitable extinguishing media**

Water with tenside additive. Water.

**5.2. Special hazards arising from the substance or mixture**

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Explosion hazard.

**6.3. Methods and material for containment and cleaning up**

Ventilate affected area.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

Keep away from sources of ignition. - No smoking.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Label-Off

Print date: 21.05.2015

Product code: 134

Page 4 of 8

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition.  
- No smoking.

##### Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

##### Eye/face protection

Tightly sealed safety glasses.

##### Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Skin protection

Protective clothing:

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

##### Test method

##### Changes in the physical state

Initial boiling point and boiling range: 60 °C

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Label-Off**

Print date: 21.05.2015

Product code: 134

Page 5 of 8

Flash point:	< 0 °C
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	7 vol. %
Ignition temperature:	300 °C
Vapour pressure: (at 20 °C)	227 hPa
Vapour pressure: (at 50 °C)	719 hPa
Density:	0,71 g/cm <sup>3</sup>

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No data available

**10.2. Chemical stability**

No data available

**10.3. Possibility of hazardous reactions**

No data available

**10.4. Conditions to avoid**

Keep away from heat. Ignition hazard.

**10.5. Incompatible materials**

No data available

**10.6. Hazardous decomposition products**

No data available

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene				
	oral	LD50	> 2000 mg/kg	Rat	
	dermal	LD50	> 2000 mg/kg	Rabbit	IUCLID
64-17-5	ethanol, ethyl alcohol				
	oral	LD50	6200 mg/kg	Rat	IUCLID
	inhalative (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS

**Additional information on tests**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**SECTION 12: Ecological information****12.1. Toxicity**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Label-Off

Print date: 21.05.2015

Product code: 134

Page 6 of 8

CAS No	Chemical name	Method	Dose	[h]   [d]	Species	Source
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene					
	Acute fish toxicity	LC50	0,7 mg/l	96 h	Pimephales promelas	
	Acute crustacea toxicity	EC50	0,42 mg/l	48 h	Daphnia magna	
64-17-5	ethanol, ethyl alcohol					
	Acute crustacea toxicity	EC50 mg/l	9268 - 14221	48 h	Daphnia magna	IUCLID

### 12.3. Bioaccumulative potential

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene	4,23
64-17-5	ethanol, ethyl alcohol	-0,31

#### Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Dispose of waste according to applicable legislation.

#### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing dangerous substances  
Classified as hazardous waste.

#### Waste disposal number of contaminated packaging


150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

#### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
Hazard label:	2.1
	
Classification code:	5F
Special Provisions:	190 327 625
Limited quantity:	1 L
Transport category:	2

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Label-Off**

Print date: 21.05.2015

Product code: 134

Page 7 of 8

Tunnel restriction code: D

**Other applicable information (land transport)**

E0

**Inland waterways transport (ADN)****14.1. UN number:** UN1950**14.2. UN proper shipping name:** AEROSOLS**14.3. Transport hazard class(es):** 2

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

**Other applicable information (inland waterways transport)**

E0

**Marine transport (IMDG)****14.1. UN number:** UN1950**14.2. UN proper shipping name:** AEROSOLS**14.3. Transport hazard class(es):** 2**14.4. Packing group:** -

Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277

EmS: F-D, S-U

**Other applicable information (marine transport)**

E0

**Air transport (ICAO)****14.1. UN number:** UN1950**14.2. UN proper shipping name:** AEROSOLS, flammable**14.3. Transport hazard class(es):** 2.1

Hazard label: 2.1



Special Provisions: A145 A167

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

**Other applicable information (air transport)**

E0

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Label-Off**

Print date: 21.05.2015

Product code: 134

Page 8 of 8

: Y203

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 62,5 % (443,75 g/l)

**National regulatory information**

Water contaminating class (D): 2 - water contaminating

**SECTION 16: Other information****Relevant R-phrases (Number and full text)**

- 10 Flammable.
- 11 Highly flammable.
- 38 Irritating to skin.
- 43 May cause sensitisation by skin contact.
- 50 Very toxic to aquatic organisms.
- 51 Toxic to aquatic organisms.
- 53 May cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.

**Relevant H- and EUH-phrases (Number and full text)**

- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*