

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Aurosteel Abdecklack blau 25ml**
Aurosteel protective lacquer blue 25 ml
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Masking material
Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Wieland Dental + Technik GmbH & Co. KG
Lindenstr. 2
75175 Pforzheim
Telefon +49 (0) 7231-37050, Telefax +49 (0) 7231-357959
- **Further information obtainable from:** msds@wieland-dental.de
- **1.4 Emergency telephone number:**
GIZ-Nord, Göttingen, Germany
+49 551 19240
Member of EPECS Network

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
ethyl acetate
acetone
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB

Trade name: Aurosteel Abdecklack blau 25ml
Aurosteel protective lacquer blue 25 ml

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients
3.2 Chemical characterisation: Mixtures

- **Description:** Solvent mixture with additives

Dangerous components:

CAS: 141-78-6	ethyl acetate	25-50%
EINECS: 205-500-4	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 67-64-1	acetone	10-<25%
EINECS: 200-662-2	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- **General information:** Take affected persons out into the fresh air.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures
5.1 Extinguishing media

- **Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

5.3 Advice for firefighters

- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures
6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
 Keep away from ignition sources.

(Contd. on page 3)

Trade name: Aurosteel Abdecklack blau 25ml
Aurosteel protective lacquer blue 25 ml

(Contd. of page 2)

- Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Fumes can combine with air to form an explosive mixture.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Store only in the original receptacle.
- **Information about storage in one common storage facility:**
Storage class 3 (Flammable liquid substances)
Only substances of the same storage class should be stored together.
Collocated storage with the following substances is prohibited:
 - Pharmaceuticals, foods, and animal feeds including additives.
 - Infectious, radioactive und explosive substances.
 - Gases.
 - Other explosive substances of storage class 4.1A.
 - Flammable solid substances or desensitized substances of storage class 4.1B.
 - Spontaneously flammable substances.
 - Substances liberating flammable gases in contact with water.
 - Strongly oxidizing substances of storage class 5.1A.
 - Ammonium nitrate and preparations containing ammonium nitrate.
 - Organic peroxides and self reactive substances.
 - Non combustible acutely toxic substances of storage class 6.1B.Under certain conditions the collocated storage with the following sub-stances is permitted (For more details see TRGS 510):
 - Oxidizing substances of storage class 5.1B.
 - Noncombustible toxic or chronically acting substances of storage class 6.1D.
 - Combustible solids of storage class 11.The substance should not be stored with substances with which ha-zardous chemical reactions are possible.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** LGK 3
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Trade name: Aurosteel Abdecklack blau 25ml
Aurosteel protective lacquer blue 25 ml

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

- Use suitable respiratory protective device in case of insufficient ventilation.
- Filter A/P2

· **Protection of hands:**



Protective gloves

· **Material of gloves**

- Butyl rubber, BR
- Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Not suitable are gloves made of the following materials:**

- Nitrile rubber, NBR
- PVC gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

Trade name: Aurosteel Abdecklack blau 25ml
Aurosteel protective lacquer blue 25 ml

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Fluid
· Colour:	Blue
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· Change in condition

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	Undetermined.

· **Flash point:** -20 °C

· **Ignition temperature:** 460 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

· Lower:	2.1 Vol %
· Upper:	13.0 Vol %

· **Vapour pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 0.96 g/cm³ (DIN 53217)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with water:**

Partly miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

· Viscosity:

· Dynamic:	Not determined.
· Kinematic at 20 °C:	60 s (DIN 53211/4)

· Solvent content:

· **Organic solvents:** 60.0 %

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with acids, alkalis and oxidising agents.

Exothermic reaction.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 6)

Trade name: Aurosteel Abdecklack blau 25ml
Aurosteel protective lacquer blue 25 ml

(Contd. of page 5)

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**

· **Acute toxicity**

· **LD/LC50 values relevant for classification:**

141-78-6 ethyl acetate

Oral	LD50	4100 mg/kg (Mouse) 4935 mg/kg (Rabbit) 5620 mg/kg (rat)
Inhalative	LC50/4 h	1600 mg/l (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rbt)

· **Primary irritant effect:**

· **Skin corrosion/irritation** No irritant effect.

· **Serious eye damage/irritation** Irritating effect.

· **Respiratory or skin sensitisation** No sensitising effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

141-78-6 ethyl acetate

EC10	2900 mg/l (16h) (<i>Pseudomonas putida</i>)
ErC50	717 mg/l (48h) (<i>Daphnia magna</i> (water flea))
IC50	3300 mg/l (48h) (<i>desmodesmus suspictatus</i>)
LC50	230 mg/l (96h) (fish)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential**

141-78-6 ethyl acetate

Bioaccumulation	log Pow: 0.73 (-) (distribution coefficient: n-octanol/Water)
-----------------	---

· **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 7)

Trade name: Aurosteel Abdecklack blau 25ml
Aurosteel protective lacquer blue 25 ml

(Contd. of page 6)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.

· **Uncleaned packaging:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

· **Recommended cleansing agents:**

Water, if necessary together with cleansing agents.
Alcohol

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1263

· **14.2 UN proper shipping name**

· **ADR** 1263 PAINT (vapour pressure at 50 °C not more than 110 kPa)
· **IMDG, IATA** PAINT

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

· **Danger code (Kemler):** Warning: Flammable liquids.
33
· **EMS Number:** F-E,S-E

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

(Contd. on page 8)

Trade name: Aurosteel Abdecklack blau 25ml
Aurosteel protective lacquer blue 25 ml

(Contd. of page 7)

· Transport/Additional information:**· ADR**

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **Transport category**
- **Tunnel restriction code**

2
D/E**· IMDG**

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":**

UN1263, PAINT (vapour pressure at 50 °C not more than 110 kPa), 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations:**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

- *** Data compared to the previous version altered.**